

## 23x152 mm ARSENAL Air Defense System ADS-N (for Navy)

23x152 mm ADS-N NSN: 1005-50-000-7416

**ADS-N** is a powerful weapons system mounted to boats/ships/watercraft, intended for destruction of air targets within the range of 2500 m at height 1500 m, light armored sea targets and shore firing points within the range of 2000 m, well as for destruction of enemy light armor vehicles, manpower/troops in the open or behind light concealment.

## **ADS-N Performance:**

- The weapon is used for destruction of air, light armored ground/sea targets, firing points, as well as for destruction of enemy manpower at open or behind the light concealment;
- Possess high tactical characteristics necessary for fighting against targets of opportunity and high speed targets;
- Equipped with Anti-Aircraft Automatic Sight ZAP-23 and Optical Ground Sight T-3;
- Weapon feeding is performed by 50 round metal linked belt placed in a metal ammunition box.
- The System uses 23x152 mm HEI-T, HEI, API-T and FAPDS-T rounds.
- Attachment of ADS-N to the deck is performed by 16 sets of bolts, nuts, thickening washers and spring washers, as the length of the bolts is according to the thickness of the deck.
- Near the ADS-N System, at place suitable for gunner operation and not disturbing the System functioning, 2 pcs
  of cabinets for keeping the ammunition boxes (for left and right hand feeding) and bath for Barrel cooling are
  mounted.



COMPLETE SET (ACCESSORIES)	ADS-N
2 pcs spare barrels	Overall protection cover
Sights: ZAP-23 , T-3 and KV-L collimator	2 pcs covers for the flush hiders
14 pcs ammunition boxes	Cover for the sight
Barrel cooling basin	2 pcs ammunition preservation cases
SPTA set	

## 23x152 mm ARSENAL Air Defense System ADS-N (for Navy)

SPECIFICATIONS	ADS-N
Number x caliber of automatic guns, mm	2x23
Ammunition, mm	23x152
Rate of fire, rounds/min	from 1600 to 2000
Muzzle velocity of projectile, m/s	970
Effective range, m	
- traverse	2000 m
- elevation	1500 m
- slant	2500 m
Combat ammunition load, pcs	100
Aiming speed, deg/s	
- traverse	30/60
- elevation	40
Engagement section, degrees	
- horizontal	360
- vertical	from -10 to +90
Overall dimensions in combat position, mm/in	
- length	3700 mm / 145.6 in
- height	1650 mm / 64.9 in
- width	1900 mm / 74.8 in
Weight of the system with covers, loaded ammunition boxes and SPTA set, kg/lbs.	880 kg / 1940.0 lbs.

PACKING	
1. Case for two barrels and one gun, pcs	2
- Case dimensions, mm/in	2135 x 385 x 336 mm / 84.0 x 15.1 x 13.2 in
- Case gross weight, kg/lbs.	150 kg / 330.6 lbs.
2. Ammunition preservation case w/ 6 pcs. boxes each	2
- Case dimensions, mm/in	1000 x 620 x 620 mm / 39.3 x 24.4 x 4.4 in
- Case gross weight, kg/lbs.	150 kg / 330.6 lbs.
3. Case for barrel cooling basin, pc	1
- Case dimensions, mm/in	1000 x 620 x 620 mm / 39.3 x 24.4 x 24.4 in
- Case gross weight, kg/lbs.	150 kg / 330.6 lbs.
4. Case with 630 belt links, pc	1
- Case dimensions, mm/in	1126 x 310 x 342 mm / 44.3 x 12.2 x 13.4 in
- Case gross weight, kg/lbs.	55 kg / 121.2 lbs.
5. Case for SPTA set, pc	1
- Case dimensions, mm/in	802 x 490 x 275 mm / 31.5 x 19.2 x 10.8 in
- Case gross weight, kg/lbs.	50 kg / 110.2 lbs.
6. Weight of mount with cover on palette, kg/lbs.	730 kg / 1609.3 lbs.
- Palette dimensions, mm/in	3100 x 2000 x 1800 mm / 122.0 x 78.7 x 70.8 in