

5.56x45 mm &7.62x39 mm ARSENAL Assault Rifles AR-M14F w/ right-side folding stock (16.3" barrel)

5.56x45 mm AR-M14F NSN: 1005-50-001-4411 7.62x39 mm AR-M14F NSN: 1005-50-001-4412

The 5.56x45 mm and 7.62x39 mm **AR-M14F** models are highly effective, milled receiver, select fire weapons with a right-side folding tubular stock and ambidextrous safety. The stock folding to the right permits any rail mounted optic to remain on the weapon when folded, not an option for left side folding models. The ambidextrous safety also allows manipulation of the safety even when the stock is in the folded position. This model in 7.62x39 is has a custom build for the DOS with QD package.

Main Features:

- Milled receiver, made from hot die forged solid blank followed by milling operations.
- Chrome lined, cold hammer forged barrel providing an extremely durable and long lasting barrel that also allows for use of corrosive and surplus ammunition if needed
- Circle 10 magazines the best, strongest, and most reliable AK magazine available
- Lower hand guard, Upper hand guard, and Pistol grip, made from glass fiber reinforced polycaproamide.
- Lower hand guard, equipped with Rails MIL-STD 1913 (Picatinny) on three sides (at the 3, 6 and 9 o'clock positions).
- **Extras (Paid Separately):**
 - 7.62x39 models black polymer magazines for 10 and 40 cartridges;
 - 5.56x45 models 20 round magazines optional
 - Magazine packages (multiple mags per rifle

 can be customized)
 - Front Sight Elevation tool 1:10;
 - set for magazines coupling;
 - Muzzle device (compensator, flash hider, muzzle brake);

- Upper hand guard, equipped with one Picatinny rail (at the 12 o'clock position).
- Tritium Self-illuminated Night Sight (3-dot sight system) - extra, used for quick target acquisition at low-light conditions.
- Metal right-side folding stock.
- Rail on the receiver for attaching optic mounts
- Additional left fire mode Selector Lever, for rapid fire mode changing and for convenience of left-handed shooters.
- blank fire attachment (BFA);
- rail mount for optics (model specific SM-13/SM-22)
- Railed handguards for accessory attachments (forward grip, flashlights, QD sling, etc.);
- QD Package allows use of QD ports and attachments for modern QD slings;
- Repair Kit packages available

The Assault Rifle design allows the attachment of 40x46mm ARSENAL UBGL-M6 and UBGL-M8, 40mm ARSENAL UBGL or GP-25 KASTYOR Underbarrel Grenade Launchers, and firing with them.



5.56x45 mm & 7.62x39 mm ARSENAL Assault Rifles AR-M14F w/ right-side folding stock

SPECIFICATIONS	AR-M14F	AR-M14F
Calibre, mm	5.56	7.62
Cartridge, mm	5.56x45	7.62x39
Fire mode	single and automatic	single and automatic
Rate of fire, rounds/min	600	600
Practical rate		
- automatic fire, rounds/min	up to 100	up to 100
- single fire, rounds/min	up to 40	up to 40
Muzzle velocity, m/s		
- bullet type M 193	910	910
- bullet type SS 109	870	
Sighting range, m	up to 800	up to 800
Maximum firing range, m	1350	1350
Effective firing range, m	500	400
Magazine capacity, rounds	30	30
Barrel length, mm/in	415 mm / 16.3 in	415 mm / 16.3 in
Sight radius, mm/in	370 mm / 14.5 in	370 mm / 14.5 in
Overall length, mm/in		
- with extended butt	970 mm / 38.1 in	970 mm / 38.1 in
- with folded butt in travelling position	720 mm / 28.3 in	720 mm / 28.3 in
Weight, kg/lbs.		
- rifle without magazine	3.75 kg / 8.26 lbs.	3.75 kg / 8.26 lbs.
- loaded magazine, kg/lbs.	0.58 kg / 1.27 lbs.	0.72 kg / 1.58 lbs.
Principle of function	gas operated automatic rifle	gas operated automatic rifle
System life, rounds	15 000	15 000

ACCESSORIES		
Cleaning rod	Magazines 4 pcs. 5.56x45 mm 7.62x39 mm	
Cleaning rod extension	Oil can	
Sling	Bag for magazines	
Box with accessories (brush, drift, slush brush, screwdriver)	Sight carrier with rails MIL-STD 1913 (Picatinny)	

PACKING		
Number of rifles in one wooden case	10	
Case dimensions, mm /in	1380 x 572 x 387 mm / 54.3 x 22.5 x 15.2 in	
Weight of the wooden case, kg/lbs.	94 kg / 207.2 lbs.	
Volume of the wooden case, m³	0.28 m	