

**5.56x45 mm AR-M2T**  
**NSN: 1005-50-001-4614**

**7.62x39 mm AR-M2T**  
**NSN: 1005-50-001-5194**

The 5.56x45 mm and 7.62x39 mm **AR-M2T** are highly effective, milled receiver, select fire weapons with a telescopic stock, railed handguards for accessory mounting, and an ambidextrous safety. The stock has four different positions and has the correct angle on the lower tang to allow for proper check weld.

#### **Main Features:**

- Milled receiver, made from hot die forged solid blank followed by milling operations.
- Chrome lined, cold hammer forged barrel providing an extremely durable and long lasting barrel that also allows for use of corrosive and surplus ammunition if needed
- Circle 10 magazines – the best, strongest, and most reliable AK magazine available.
- The Upper hand guard, equipped with one Picatinny rail (at the 12 o'clock position).
- The Lower hand guard, equipped with Rails MIL-STD 1913 (Picatinny) on three sides (at the 3, 6 and 9 o'clock positions).
- Lower hand guard, Upper hand guard, and Pistol grip, made from glass fiber reinforced polycapromide.
- Rail on the receiver for attaching optic mounts
- Telescopic stock with 4 positions.
- Additional left fire mode Selector Lever, for rapid fire mode changing and for convenience of left-handed shooters

#### **Extras (Paid Separately):**

- Tritium Self-illuminated Night Sight (3-dot sight system);
- 7.62x39 models - black polymer magazines for 10 and 40 cartridges;
- 5.56x45 models – 20 round magazines optional
- Magazine packages (multiple mags per rifle – can be customized);
- Front Sight Elevation tool 1:10;
- set for magazines coupling;
- blank fire attachment (BFA);
- Rail mount for optics (model specific SM-13/SM-22);
- Railed handguards for accessory attachments (forward grip, flashlights, QD sling, etc.);
- QD Package – allows use of QD ports and attachments for modern QD slings;
- Repair Kit packages available

The Assault Rifle design allows the attachment of 40x46mm UBGL-M6, UBGL-M8 and 40 mm UBGL-1 ARSENAL Underbarrel Grenade Launchers and firing with them.



## 5.56x45 & 7.62x39 mm ARSENAL Assault Rifles AR-M2T telescopic stock

SPECIFICATIONS	AR-M2T	AR-M2T
Calibre, mm	5.56	7.62
Cartridge, mm	5.56x45	7.62x39
Fire mode	single and automatic	single and automatic
Rate of fire, rounds/min	600	600
Practical rate, rounds/min - automatic fire	up to 100	up to 100
- single fire	up to 40	up to 40
Muzzle velocity, m/s		650
- bullet type M 193	880	-
- bullet type SS 109	830	-
Sighting range, m	up to 500	up to 500
Maximum firing range, m	1100	1100
Effective firing range, m	400	350
Magazine capacity, rounds	30	30
Barrel length, mm/in	320 mm / 12.59 in	320 mm / 12.59 in
Sight radius, mm/in	278 mm / 10.9 in	278 mm / 10.9 in
Overall length, mm/in		
- with stock unfolded	952 mm / 37.48 in	952 mm / 37.48 in
- with stock folded	852 mm / 33.54 in	852 mm / 33.54 in
Weight, kg/lbs.:		
- rifle without magazine	4.0 kg / 8.8 lbs.	4.0 kg / 8.8 lbs.
- loaded magazine	0.58 kg / 1.27 lbs.	0.72 kg / 1.58 lbs.
System life, rounds	15 000	15 000
Principle of function	gas operated	gas operated

ACCESSORIES	
Cleaning rod and Cleaning rod extension	Oil can
Box with accessories (brush, drift, slush brush (cal. 5.56)/ scourer (cal. 7.62), screwdriver)	Magazines 4 pcs. 5.56x45 mm 7.62x39 mm
Sling	Bag for magazines

PACKING	
Number of rifles in one wooden case	10
Case dimensions, mm/in	1380 x 530 x 387 mm / 54.3 x 20.8 x 15.2 in
Weight of the wooden case, kg/lbs.	86 kg / 189.6 lbs.
Volume of the wooden case, m <sup>3</sup>	0.28 m