

5.56x45mm AR-M5T
NSN: 1005-50-001-4434

7.62x39mm AR-M5T
NSN: 1005-50-001-4431

The 5.56x45 mm and 7.62x39 mm **AR-M5T** are highly effective, milled receiver, select fire weapons with a telescopic stock and AR-M5F picatinny rail for optics mounting. Additional rails are located on the handguards for attachment of light, lasers, etc. The stock has four different positions and has the correct angle on the lower tang to allow for proper check weld.

Main Features:

- Milled receiver, made from hot die forged solid blank followed by milling operations.
- Chrome lined, cold hammer forged barrel providing an extremely durable and long lasting barrel that also allows for use of corrosive and surplus ammunition if needed
- Circle 10 magazines – the best, strongest, and most reliable AK magazine available
- The Lower hand guard, equipped with Rails MIL-STD 1913 (Picatinny) on three sides (at the 3, 6 and 9 o'clock positions).
- The Upper hand guard, equipped with one Picatinny rail (at the 12 o'clock position).
- Tritium Self-illuminated Night Sight (3-dot sight system) - extra, used for quick target acquisition at low-light conditions.
- AR-M5F rail system is secured to the receiver allowing for the most stable platform available to attach optics
- Telescopic plastic stock with several stages of extraction.
- Additional left fire mode Selector Lever, for rapid fire mode changing and for convenience of left-handed shooters

Extras (Paid Separately):

- 7.62x39 models - black polymer magazines for 10 and 40 cartridges;
- 5.56x45 models – 20 round magazines optional;
- Magazine packages (multiple mags per rifle – can be customized);
- Front Sight Elevation tool 1:10;
- set for magazines coupling;
- Muzzle device (compensator, flash hider, muzzle brake);
- Bayonet;
- blank fire attachment (BFA);
- QD Package – allows use of QD ports and attachments for modern QD slings;
- Repair Kit packages available

The Assault Rifle design allows the attachment of 40x46mm UBGL-M6, UBGL-M8 and 40 mm UBGL-1 ARSENAL Underbarrel Grenade Launchers and firing with them.



5.56x45 & 7.62x39 mm ARSENAL Assault Rifles AR-M5T w/ telescopic stock

SPECIFICATIONS	AR-M5T	AR-M5T
Calibre, mm	5.56	7.62
Cartridge, mm	5.56x45	7.62x39
Fire mode	single and automatic	single and automatic
Rate of fire, rounds/min	600	600
Practical rate, rounds/min - automatic fire	up to 100	up to 100
- single fire	up to 40	up to 40
Muzzle velocity, m/s		710
- bullet type M 193	910	-
- bullet type SS 109	870	-
Sighting range, m	up to 800	up to 800
Maximum firing range, m	1350	1350
Effective firing range, m	500	400
Magazine capacity, rounds	30	30
Barrel length, mm/in	415 mm / 16.3 in	415 mm / 16.3 in
Sight radius, mm/in	370 mm / 14.5 in	370 mm / 14.5 in
Overall length, mm/in		
- with extended stock	1045 mm / 41.1 in	1045 mm / 41.1 in
- with collapsed stock	945 mm / 37.2 in	945 mm / 37.2 in
Weight, kg/lbs.:		
- rifle without magazine	4.2 kg / 9.26 lbs.	4.2 kg / 9.26 lbs.
- loaded magazine	0.58 kg / 1.27 lbs.	0.72 kg / 1.58 lbs.
System life, rounds	15 000	15 000
Principle of function	gas operated	gas operated

ACCESSORIES	
Cleaning rod	Bag for magazines
Sling	Oil can
Box with accessories (brush, drift, slush brush (cal. 5.56)/ scourer (cal. 7.62), screwdriver)	Magazines 4 pcs. 5.56x45 mm 7.62x39 mm

PACKING	
Number of rifles in one wooden case	10
Case dimensions, mm/in	1270 x 572 x 387 mm / 50.0 x 22.5 x 15.2 in
Weight of the wooden case, kg/lbs.	95 kg / 209.4 lbs.
Volume of the wooden case, m ³	0.31 m