

5.56x45 mm & 7.62x39 mm ARSENAL Light Machine Guns **LMG-F** w/ underfolding stock (23.2" barrel)

5.56x45 mm LMG-F
NSN: 1005-50-000-0718

7.62x39 mm LMG-F
NSN: 1005-50-000-0646

The 5.56x45 mm and 7.62x39 mm **LMG-F** models are highly effective, milled receiver, select fire weapons (RPK's). Comparable to the U.S. Military M249 SAW, this is a lightweight machine gun used for covering or suppressive fire against personnel and light armament at a much greater distance than a standard AK due to the 23.2" barrel. The underfolding stock allows for easier storage or transportation and also allows easier use when firing from cramped spaces.

Main Features:

- Milled receiver, made from hot die forged solid blank followed by milling operations.
- Chrome lined, cold hammer forged barrel providing an extremely durable and long lasting barrel that also allows for use of corrosive and surplus ammunition if needed
- Circle 10 magazines – the best, strongest, and most reliable AK magazine available
- Lower hand guard, Upper hand guard, and Pistol grip, made from glass fiber reinforced polycapromide.
- Tritium Self-illuminated Night Sight (3-dot sight system)
- Collapsible bipod.
- Underfolding stock - modern straight-back stock, not slanted
- Windage adjustable rear sight
- SAW style grip

Extras (Paid Separately):

- Tritium Self-illuminated Night Sight (3-dot sight system);
- 7.62x39 models - black polymer magazines for 40 cartridges;
- Front Sight Elevation tool 1:10;
- Magazine packages (multiple mags per rifle – can be customized)
- set for magazines coupling;
- blank fire attachment (BFA);
- rail mount for optics
- rail for sighting devices.
- QD Package – allows use of QD ports and attachments for modern QD slings;
- Repair Kit packages available



5.56x45 mm & 7.62x39 mm ARSENAL Light Machine Guns LMG-F w/ underfolding stock

SPECIFICATIONS	LMG	LMG
Calibre, mm	5.56	7.62
Cartridge, mm	5.56x45	7.62x39
Fire mode	single and automatic	single and automatic
Rate of fire, rounds/min	600	600
Practical rate, rounds/min		
- automatic fire	150	150
- single fire	50	50
Muzzle velocity, m/s		750
- bullet type M 193	980	-
- bullet type SS 109	930	-
Sighting range, m	Up to 1000	up to 1000
Maximum firing range, m	Up to 2000	up to 1500
Effective firing range, m	600	500
Magazine capacity, rounds	30	40
Barrel length, mm/in	590 mm / 23.2 in	590 mm / 23.2 in
Sight radius, mm/in	555 mm / 21.8 in	555 mm / 21.8 in
Overall length, mm/in		
- with unfolded stock	1060 mm / 41.7 in	1060 mm / 41.7 in
- with folded stock	825 mm / 32.4	825 mm / 32.4
Weight, kg/lbs.:		
- rifle without magazine	4.82 kg / 10.6 lbs.	4.82 kg / 10.6 lbs.
- loaded magazine	0.58 kg / 1.27 lbs.	0.92 kg / 2.02 lbs.
System life, rounds	20 000	20 000
Principle of function	gas operated	gas operated

ACCESSORIES	
Cleaning rod	Sling
	Oil Can
2 pcs. bags for 4 magazines	Box with accessories (brush, drift, scourer (cal. 5.56) slush brush (cal. 7.62), screwdriver)
8 pcs. magazines for 30 cartridges (cal. 5.56) 5.56x45 mm	8 pcs. magazines for 40 cartridges (cal. 7.62) 7.62x39 mm
Individual kit of spare parts consisting of:	
Extractor; Extractor's spring; Firing pin	Bag for spare parts

PACKING	
Number of rifles in one wooden case	6
Case dimensions, mm/in	1190 x 650 x 400 mm / 46.8 x 25.5 x 15.7 in
Weight of the wooden case, kg/lbs.	82 kg / 180.7 lbs. (5.56x45mm) 84 kg / 185.1 lbs. (7.62x69 mm)
Volume of the wooden case, m ³	0.31 m